

NEUTRAL TRAFFIC FILM REMOVER

NT20

TECHNICAL INFORMATION SHEET

PRODUCT DESCRIPTION

NT20 Neutral Traffic Film Remover is a high performance advanced detergent based traffic film remover and floor cleaning product. Specially formulated with a high active blend of emulsifiers giving a long lasting, mild foam leaving a wax shine and a streak free finish.

FEATURES AND BENEFITS

- A high performance neutral based detergent leaving a high wax shine and a streak free finish on all vehicle types.
- NON-CAUSTIC FORMULA
- Powerful formula removes the toughest of dirt.
- Cleans and degreases vehicle bodies, chassis and alloy wheels.
- Effective to use on all vehicle types including cars, vans, trucks and industrial vehicles.
- Effective to use on all types of Emergency Services vehicles as the powerful formula will not deaden paintwork and damage vehicle decals.
- Multi-purpose product can be used as a floor cleaner.

INSTRUCTIONS FOR USE

DILUTION

Pump Action Dispenser: Add water to bucket. Add 3 pump measures to clean.

Blend Centre: Fill bucket with pre-diluted solution.

Fixed Area Wash/Automatic Vehicle Wash

1. Use at a concentration of 1 part to 150 parts water, or by following the manufacturer's instructions.



HEALTH & SAFETY



HAZARD AS SUPPLIED:

Causes Eye Irritation.
Wear Gloves For Prolonged Use.

HEALTH & SAFETY



HAZARD WHEN USED AT RECOMMENDED DILUTION:

Not Classified.
Wear Gloves For Prolonged Use.

PACK SIZES

SKU	Pack Size
571054	2x5L
571055	20L

Steam Cleaning, Hot or Cold Pressure Washing

1. Use at a concentration of 1 part to 150 parts water, or by following the manufacturer's instructions.
2. Lightly wet the vehicle.
3. Spray on the NT20 Neutral Traffic Film Remover using even sweeps of the lance.
4. Turn off the detergent feed and thoroughly rinse the vehicle.

Manual Washing

1. Use at a concentration of 1 part to 150 parts water.
2. Lightly wet the vehicle.
3. Apply the solution generously with a sponge, cloth or vehicle exterior wash brush, starting at the highest point to be cleaned.
4. Rinse the vehicle thoroughly.
5. Allow the vehicle to dry or alternatively mop up the surplus liquid with a well wrung out sponge, cloth or leather.

Floor Cleaning – Manual

1. Use at a concentration of 1 part to 80 - 150 parts water.
2. Dose the product into a bucket filled with water and mop the floor to apply the solution.
3. Allow the product to act briefly and scrub, brush or mop depending on the type of soiling.
4. Remove the soiled solution from the floor with a clean mop.

Floor Cleaning – Machine – Light to Medium Soiling

1. Use at a concentration of 1 part to 80 - 150 parts water.
2. Dose the product into the full water tank of a single disc machine or scrubber drier and apply the solution to the floor surface.
3. Allow the product to act briefly and scrub, depending on the type of soiling.
4. Remove the soiled solution from the floor.

Floor Cleaning – Machine – Heavy Soiling

1. Use at a concentration of 1 part to 80 - 150 parts water.
2. Dose the product into the full water tank of a single disc machine or scrubber drier and apply the solution to the floor surface.
3. Scrub the floor without wet vacuuming. Allow the product to act briefly depending on the type of soiling.
4. Scrub a second time and directly wet vacuum the soiled solution.

SAFE HANDLING AND STORAGE

See visual information on page 1.

Full guidance on the handling and safe use of the product can be obtained from the Safety Data Sheet.

Store in original container.

Avoid extremes of temperature.

TECHNICAL INFORMATION

Appearance:	Orange liquid.
pH:	7.0.
Odour:	Barely Perceptible.
Solubility:	Fully miscible in water.
Environmental:	100% Bio Degradable.

The above data is typical of normal production and should not be taken as a specification.

MATERIALS COMPATIBILITY

Under recommended conditions of use NT20 Neutral Traffic Film Remover is suitable for use on most materials commonly encountered in traffic environments.

OTHER INFORMATION

